

HN198DP



LCD Panel	Display size	19" (48,26 cm)	
	Panel Type	Active Matrix TFT	
	Brightness	250 cd/m ² (typ.)	
	Contrast	700:1 (typ.)	
	Pixel pitch	0.294(H)*0.294(V) mm	
	Resolution (H x V)	SXGA 1280 x 1024	
	Response time	8 ms (typ.)	
	View angles LR,UD	H/V 150°/135°	
	Display colors	16.2M Colors	
	Color	9300K, 6500K, User Mode	
	Input	Display Surface	Anti-Glare
		Input 1	D-Sub, Audio
Input 2		DVI-D	
Output	Input 3		
	Output 1		
	Output 2		
Power	Headphone		
	Speakers	1W x 2	
	Supply	AC 100~240V, 50~60Hz	
Operating Condition	Consumption	37 W (typ.)	
	Temperature	5 ~ 35°C	
Physical	Humidity	10 ~ 85%	
	Dimension (W*D*H)	417 x 219 x 545 mm	
	Packing dimension (W*D*H)	490 x 175 x 522 mm	
	Net weight	5.7 kg	
	Gross weight	8 kg	
	Tilt	0°~ 20°	
	Kensington Lock	Yes	
	VESA mounting	VESA Standard, 100mm	
Controls	Front control	Auto, Vol(-), Power/LED, Vol(+), Menu	
	On screen display	EN, SC, TC, DE, FR, IT, ES, JS	
Certification	Safety	UL/CUL, CB, GS, CCC, BSMI, FCC, CE	
	Emission	TCO03	
Extras 1	Power saving	EPA Energy Star	
	Extras 2	Height Adjustable	
	Extras 3	Pivot	
Accessories		powercord, VGA cable, audio cable, users manual (CD), quickstart guide (paper), warranty card	

Specifications are subject to change without notice. Error accepted.